


SPEARHEAD


MULTICUT 620



MULTICUT 620 FEATURES



- AGRICULTURE
- PASTURE
- LIGHT SCRUB
- HEAVY SCRUB
- AIRFIELD
- HIGHWAYS
- STUBBLE MANAGEMENT



The Multicut 620 is boosted with additional output capability, enabling the comfortable clearance of more than 8 hectares per hour.

A walking axle design is standard across the full width of the machine delivering exceptional ground contour following and reduced shock loading in harsh field conditions.

Wider wheels are also fitted to add additional comfort and improved performance.

Spearhead's renowned durability is built into this mower and the evenness of spread from the five rotors is unrivalled leaving a clean finish and high output unmatched by competitive three rotor machines of the same width.

With a six gearbox driveline, each with slip clutch protection, the power is evenly spread to deliver exceptional reliability and durability whilst allowing enhanced forward speeds and fuel efficiency.

MULTICUT 620	HP	540 1000			HP				
	TRACTOR HP	PTO SPEED	TRANSPORT WIDTH	CUTTING WIDTH	GEARBOX RATING	NO. OF WHEELS	NO. OF ROTORS	NO. OF BLADES	CUTTING HEIGHT
	90hp	1000rpm	2.70m / 106"	6.28m / 247"	250hp & 111hp	8	5	15	25 - 210mm 1" - 8 1/4"
UNIT OPTIONS									
	6 BLADE KIT (FLAT BLADES)	HYDRAGAS SUSPENSION	6, 8 or 21 SPLINE PTO	SWIVEL TOWING EYE	K80 TOWING HITCH				

SPECIFICATION		MULTICUT 620	
Machine weight*	2850kg / 6283lbs	Gearbox oil capacity [outer rotor gearboxes (x2)]	1.3 litres / 2.3 pints
Hitch	Multi-positional drawbar	Deck construction	All welded construction
Cutting width	6.28m / 247"	Deck material thickness	6mm (1/4")
Working machine width	6.47m / 255"	Side skirt material thickness	5mm (3/16")
Transport machine width	2.70m / 106"	Skid construction	Replaceable bolt on skid shoes
Maximum working length	5.07m / 200"	Anti-scalp dish [centre rotor + inner wing rotors]	6mm (1/4") round pan with blade holder bar
Transport length	4.93m / 194"	Anti-scalp dish [outer wing rotors]	5mm (3/16") round pan with blade holder bar
Deck height**	0.23m / 9"	Blades (x15)	12mm (1/2") 30 Carbon Boron hardened and tempered. Free swinging high lift - low friction
Transport height	2.90m / 115"	Blade bolts	M24 C/W shank grade 8.8
Cutting height	25mm - 210mm (1" - 8 1/4")	Blade tip speed (1000rpm)	79mps / 15551fpm
Cutting capacity	100mm / 4"	Driveline	ASAE Category 6
Recommended tractor HP	90hp / 67kW	Driveline protection	2/4-way slip clutches on rotor gearboxes. Overrun on input shaft
Wing working angles	45° up / 15° down	Tailwheel mount assemblies	Tubular welded walking axles
Power take-off speed	1000rpm	Tailwheels (x8)	21x9 14 PLY optional wider pneumatic tyre with steel hub
Gearbox [splitter]	Cast Iron housing	Front guard	Single chain guards on each deck
Gearbox [rotor gearboxes (x5)]	Cast Iron housing		
Input shaft	1" 3/8 Z21 or Z6 SFT 8 tractor end		
Gearbox lubricant	EP80-90W or GL-4 / GL-5 oil		
Gearbox oil capacity [splitter gearbox]	2.7 litres / 4.7 pints		
Gearbox oil capacity [centre + inner rotor gearboxes (x3)]	2.1 litres / 3.7 pints		

*With front and rear single chain guards ** Underside of deck to skid

SPEARHEAD

📍 Station Road, Salford Priors, Evesham, Worcestershire, WR11 8SW, England ☎ +44 (0)1789 491860

✉ enquiries@spearheadmachinery.com 📧 spearheadmachinery.com 🐦 📘 SpearheadWorld



designed and built in
GREAT BRITAIN



Spearhead
is a member of the
Alamo Group

